AXIS T94P01L

For indoor and outdoor recessed mounting

AXIS T94P01L Recessed Mount enables sleek, elegant and discreet recessed ceiling installations together with AXIS M5525-E PTZ Network Camera. It is suitable for air-handling spaces in indoor installations as the back box is made of metal and has a 3/4" (M25) hole for protected cable-runs in conduits. When the camera is attached to the recessed mount it is embedded into the ceiling, revealing only the camera dome and the low-profile cover ring, which is easily repaintable.

- > For recessed installations in drop ceilings and soffit
- > Indoor and outdoor use
- > Quick and easy installation





AXIS T94P01L

General	
Supported products	AXIS M5525-E PTZ Network Camera
Casing	Material: aluminum, plastic Color: white NCS S 1002-B
Sustainability	PVC free
Mounting	Recessed in drop ceilings, ceiling tiles, roof overhang/soffit
Environment	Outdoor/indoor
Cable routing	Top: 3/4" conduit entrance
Approvals	Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22 Environment IEC 60068-2-27, IEC 60068-2-6, IEC 60068-2-75, IEC 62262 IK09
Dimensions	Height inside ceiling/wall: 97.5 mm (3 27/32 in) Height outside ceiling/wall (including camera): 14 mm (35/64 in) Diameter outside ceiling/wall: ø 248 mm (9 49/64 in) Diameter cut-out in ceiling/wall: ø 215 mm (8 15/32 in)
Weight	1100 g (2.4 lb)
Maximum load	4500 g (9.9 lb)
Included accessories	Installation Guide
Optional accessories	AXIS Safety Wire 3 m
Warranty	Axis 3-year warranty, see *axis.com/warranty*

Environmental responsibility:

www.axis.com/environmental-responsibility

©2018 Axis Communications AB. AXIS COMMUNICATIONS, AXIS, and VAPIX are registered trademarks or trademark applications of Axis AB in various jurisdictions. All other company names and products are trademarks or registered trademarks of their respective companies. We reserve the right to introduce modifications without notice.