



Product:

UVC-G6-Bullet

Overview

Dimensions	Without mount: Ø82 x 88.8 mm (Ø3.2 x 3.5") With mount: Ø82 x 153 mm (Ø3.2 x 6")
IR Night Vision	30 m (98 ft)
Face Recognition	✓
License Plate Recognition	✓
Smart Detections (People, Vehicles, Animals)	✓
Resolution	4K
Field of View	H: 109.9°, V: 56.7°, D: 134.1°
Audio	Microphone
Weatherproofing	IP66
Tamper Resistance	IK04
Mounting	Wall, ceiling, pole mount (Included) Junction box, angled base (Optional)

Performance

Networking Interface	10/100 MbE RJ45 port
----------------------	----------------------

Video

Image Settings	Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay, HDR
Max. Frame Rate	30 FPS
Resolution	8MP 3840 x 2160 (16:9)

Optics

Sensor	1/1.8" 8MP
Lens	Fixed focal length
Night Mode	Built-in IR LED illumination and IR cut filter

Hardware

Max. Power Consumption	9.9W
Supported Voltage Range	37–57V DC
Power Method	PoE
Processor	Quad-core Arm® Cortex®-A53 based chip
Pole Mount Diameter	1.5–2" (38–50 mm)
Weight	Without mount: 587 g (1.3 lb) With mount: 737 g (1.6 lb)
Enclosure Material	Polycarbonate, aluminum alloy
Mount Material	Wall mount: aluminum alloy, polycarbonate Pole mount: aluminum alloy
Button	(1) Factory-reset
Ambient Operating Temperature	-20 to 50° C (-4 to 122° F)
Ambient Operating Humidity	0 to 90% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC





