Hanwha Vision



Network | Thermal


TNO-C3060T

QVGA AI Tele lens Thermal Camera

Key Features

- QVGA resolution (384x288, 17µm)
- 35mm Tele lens option
- High performance thermal sensitivity (NETD 20mK@25°C)
- AI based object classification (person, vehicle)
- Max. 30fps (H.265/H.264/MJPEG)
- IP66/67, IK10, NEMA4X, NEMA-TS2, MIL-STD-810H
- Secure element with FIPS 140-3 level3, CC EAL6+

Compatible Devices



SBP-140CMB | SBP-180CMB | SBP-180CMS | SBP-150CMP | SBP-300CMP | SBP-900CMP | SBP-C15H



SBP-C15NP | SBP-C35H | SBP-C15P | SBP-150CMI | SBP-300CMI | SBP-300CMW1 | SBP-900CMW



SBP-300CMTW | SBP-300CMTS | SBP-250WMW | SBP-400WMW | SBP-115PFA | SBP-150PMW | SBD-180PMW



SBP-156KMW | SBP-156LMW1 | SBP-050NBW | SBP-150NBW | SBP-060BA | SBP-300WMW | SBP-300WMW1

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.


SBP-160WMW1


SBP-300BW1


SBP-300PMW2


SBP-300KMW1


SBP-300LMW


SBP-300NBW

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

TNO-C3060T

QVGA AI Tele lens Thermal Camera



Specifications

Vidéo

Dispositif d'imagerie	Type	Microbolomètre non refroidi (384x288)
Résolution		768x576, 384x288
Fréquence d'images maximale	H.265/H.264	30fps
	MJPEG	30fps
Plage spectrale		8~14㎛
NETD		≤20mK@25°C, F1.0
Taille du pixel		17㎛
Sortie vidéo		USB: Micro USB Type B

Objectif

Distance focale (mm)		35
Rapport d'ouverture maximal (F number)	Grand-angle	1.0
Champ de vision angulaire	Horizontal	10.7°
	Vertical	8.0°
	Diagonale	13.3°
iFoV		0.486 mRad
Distance minimale à l'objet		36.1m(118.4ft)
Contrôle de mise au point		Fixe
Type d'objectif		Athérmique

Pan / Inclinaison / Rotation

Plage Pan / Inclinaison / Rotation	Panoramique	0°~350°
	Inclinaison	0°~90°
	Rotation	0°~350°

Fonctionnement de la caméra

Détection de mouvement	Quantité	8 pièces
	Forme	Zones polygonales à 8 points

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

Fonctionnement de la caméra

Masquage de confidentialité	Quantité	6 pièces
	Forme	Zones rectangulaires
	Couleur / Option	Gris, Noir, Blanc
Rotation vidéo		Inversion verticale, Inversion horizontale, Vue couloir (90°/270°)
Interface série		RS-485
Interface d'alarme	Entrée/Sortie	2 ports I/O configurables
	Autres	Prise en charge d'entrées/sorties d'alarme supplémentaires via boîtier I/O optionnel
Déclencheurs d'alarme		Analyse intelligente, Déconnexion réseau, Entrée d'alarme, Planification horaire, Abonnement MQTT
Événements d'alarme lors du déclenchement d'alarme		Téléversement de fichier (image) : e-mail/FTP/SFTP, Téléversement de fichier (vidéo) : FTP/SFTP, Notification : e-mail, Enregistrement : SD/SDHC/SDXC ou NAS lors du déclenchement d'événements,Sortie d'alarme, Transfert : Préréglage PTZ, MQTT : publication
Entrée audio		Sélectionnable (entrée micro / ligne)
Sortie audio		Sortie ligne
Palette de couleurs		Blanc chaud, Blackhot, Arc-en-ciel, Arc-en-ciel2, Sépia, Rouge, Fer, Personnalisé

Analytique

Type d'objet classifié		Personne, Véhicule
Vignette		Meilleure prise
Événements analytiques	Basé sur moteur IA	Détection d'objet, Ligne virtuelle (Traversée/Direction), Zone virtuelle (Errance/Intrusion/Entrée/Sortie), Détection de mouvement
	Normal	Détection de mouvement, Altération, Détection audio, Classification sonore, Détection de choc, Zone virtuelle (Apparition/Disparition)

Détection de température

Palettes hybrides	Prise en charge
Surveillance de l'état ROI	Aucun, Augmentation, Diminution

Réseau

Ethernet	Metal shielded RJ-45(10/100/1000BASE-T)
Compression vidéo	H.265/H.264: Main/Baseline/High, MJPEG
Compression audio	Sélectionnable G.711 u-law / G.726,G.726(ADPCM) 8kHz,G.711 8kHz, G.726: 16kbps,24kbps,32kbps,40kbps, AAC-LC: 48kbps at 16kHz
Codec intelligent	Manuel, WiseStream II , WiseStream III
Contrôle du débit binaire	H.265/H.264: CBR or VBR, MJPEG: VBR

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

Réseau

Streaming	Unicast	Jusqu'à 20 utilisateurs
	Multidiffusion	Prise en charge
	Streaming multiple	Jusqu'à 10 profils
Protocole		IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SFTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, CDP, SRTP(TCP, UDP Unicast), MQTT, Syslog
Interface de programmation applicative (API)	ONVIF	S, G, T, M
	Autres	SUNAPI(HTTP API), Plateforme ouverte Hanwha Vision

Sécurité

Protection de l'OS / du firmware	Firmware chiffré, Démarrage sécurisé, Firmware signé
Authentification utilisateur	Authentification Digest, Prévention des attaques par force brute
Authentification réseau	IEEE 802.1X(EAP-TLS, EAP-LEAP, EAP-PEAP, MSCHAPv2)
Communication sécurisée	HTTPS, WSS (WebSocket sécurisé), SRTP
Contrôle d'accès	Contrôle d'accès basé sur IP
Protection des données	Informations d'identification chiffrées, Compression et chiffrement pour l'exportation des fichiers d'enregistrement en direct
Audit	Gestion des journaux d'accès / système / événements
ID de l'appareil	Certificat de l'appareil (Hanwha Vision Root CA)
Stockage sécurisé	Chiffrement de partition SDcard (AES-256), Élément sécurisé
Certificat de sécurité	Élément sécurisé (FIPS 140-3 niveau 3, CC EAL6+)

Général

Mémoire	RAM	2GB
	Flash	512MB
Stockage Edge	Micro SD/SDHC/SDXC	Max. 1 To x 1 emplacement

Environnement & Électrique

Conditions de fonctionnement	Température	-40°C~+60°C(-40°F~+140°F)
	Humidité	0~95 % HR (sans condensation)
Conditions de stockage	Température	-50°C~+60°C(-58°F~+140°F)
	Humidité	0~95 % HR (sans condensation)
Tension d'entrée		PoE(IEEE802.3af, Class3), 12VDC
Consommation électrique	PoE	Max. 10.8W, typical 9W
	12VDC	Max. 9.4W, typical 7.7W

Mécanique

Couleur	Blanc
Matériau	Aluminum

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

Mécanique

Code RAL	RAL9003
Dimensions du produit	ø107.3x275mm(ø4.22x10.83")
Poids du produit	2370g(5.22lb)
Trou de conduit compatible	Prise en charge de la compatibilité du conduit via adaptateur optionnel
Boîte de dérivation compatible	Simple, Double, Octogone 4", Carré

Certifications et Normes

EMC	FCC 47 CFR 15 Sous-partie B Classe A, CE/UKCA - EN55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3, VCCI CISPR 32 Class A, RCM AS-NZS CISPR 32 Class A, KS C 9832 Class A, KS C 9835, Réglementation IC ICES-003 Édition 7 Classe A
Sécurité	UL 62368-1, CAN/CSA C22.2 NO. 62368-1
Environnement	IEC/EN 63000, IEC 60529 IP66, IEC 60529 IP67, IEC 62262 IK10, NEMA TS 2-2013 (2.2.7, 2.2.8, 2.2.9), NEMA 250 type 4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, MIL-STD-810H 501.7, MIL-STD-810H 502.7, MIL-STD-810H 507.6, MIL-STD-810H 509.7, MIL-STD-810H 514.8, MIL-STD-810H 516.8

DORI (EN62676-4 standard)

Détection (25PPM/ 8PPF)	Grand angle	1,230m(4,034.88ft)
Reconnaissance (125PPM/ 38PPF)	Grand angle	308m(1,008.72ft)
Identification (250PPM/ 76PPF)	Grand angle	154m(504.36ft)

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.


TNO-C3060T

QVGA AI Tele lens Thermal Camera



CAD

Unit: mm [inch]



Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.