DHI-VTO420XF-X Series

Module





Technical Specification	
Model	DHI-VTO4202F-MB1
System	
Main Processor	Embedded Processor
Button Type	Mechanical
Performance	
Casing Material	Aluminum alloy
Port	
Power Output	5 VDC (provides power for other modules)
General	
Appearance Color	Silver
Power Supply	5 VDC (provided by other modules)
Installation	Flush Mount; Surface Mount
Product Dimensions	100 mm × 50.0 mm × 30.50 mm (3.94" × 1.97" × 1.20")
Protection	IK07; IP65 (silicone sealant is needed for installation)
Operating Temperature	–30 °C to +60 °C (–22 °F to +140 °F)
Operating Humidity	10%–90% (RH)
Power Consumption	≤0.5 W
Gross Weight	0.18 kg (0.40 lb)

Technical Specification	
Model	DHI-VTO4202F-MB2
System	
Main Processor	Embedded Processor
Button Type	Mechanical
Performance	
Casing Material	Aluminum alloy
Port	
Power Output	5 VDC (provides power for other modules)
General	
Appearance Color	Silver
Power Supply	5 VDC (provided by other modules)
Installation	Flush Mount; Surface Mount
Product Dimensions	100 mm × 50.0 mm × 30.50 mm (3.94" × 1.97" × 1.2")
Protection	IK07; IP65(silicone sealant is needed for installation)
Operating Temperature	–30 °C to +60 °C (–22 °F to +140 °F)
Operating Humidity	10%–90% (RH)
Power Consumption	≤0.5 W
Gross Weight	0.17 kg (0.37 lb)





Technical Specification	
Model	DHI-VTO4202F-MB5
System	
Main Processor	Embedded Processor
Button Type	Mechanical
Performance	
Casing Material	Aluminum alloy
Port	
Power Output	5 VDC (provides power for other modules)
General	
Appearance Color	Silver
Power Supply	5 VDC (provided by other modules)
Installation	Flush Mount; Surface Mount
Product Dimensions	100 mm × 100 mm × 30.50 mm (3.94" × 3.94" × 1.2")
Protection	IK07; IP65(silicone sealant is needed for installation)
Operating Temperature	–30 °C to +60 °C (–22 °F to +140 °F)
Operating Humidity	10%–90% (RH)
Power Consumption	≤0.5 W
Gross Weight	0.31 kg (0.68 lb)

Technical Specification	
Model	DHI-VTO4202F-MDB2
System	
Button Type	Mechanical
Number of Buttons	2
Performance	
Casing Material	Aluminum alloy
Port	
Power Output	5 VDC (Provide power for other modules)
General	
Appearance Color	Silver
Power Supply	5 VDC (Provided with power by other modules)
Certifications	CE EMC; CE LVD
Product Dimensions	100.0 mm × 50.0 mm × 26 mm (3.94" × 1.97" × 1.02")
Protection	IK07; IP65 (Silicone sealant is needed for installation)
Operating Temperature	–30 °C to +60 °C (–22 °F to +140 °F)
Operating Humidity	10%–90% (RH), non-condensing
Operating Environment	Outdoor
Operating Altitude	0 m–3,000 m (0 ft–9,842.52 ft)
Power Consumption	≤0.2 W (standby), ≤0.6 W (working)
Gross Weight	0.23 kg (0.51 lb)
Storage Temperature	0 °C to +40 °C (+32 °F to +104 °F)
Storage Humidity	30%–75% (RH)





Technical Specification	
Model	DHI-VTO4202F-MDB4
System	
Button Type	Mechanical
Number of Buttons	4
Performance	
Casing Material	Aluminum alloy
Port	
Power Output	5 VDC (Provide power for other modules)
General	
Appearance Color	Silver
Power Supply	5 VDC (Provided with power by other modules)
Certifications	CE EMC; CE LVD
Product Dimensions	100.0 mm × 50.0 mm × 26 mm (3.94" × 1.97" × 1.02")
Protection	IK07; IP65 (Silicone sealant is needed for installation)
Operating Temperature	–30 °C to +60 °C (–22 °F to +140 °F)
Operating Humidity	10%–90% (RH), non-condensing
Operating Environment	Outdoor
Operating Altitude	0 m–3,000 m (0 ft–9,842.52 ft)
Power Consumption	≤0.2 W (standby), ≤0.6 W (working)
Gross Weight	0.24 kg (0.53 lb)
Storage Temperature	0 °C to +40 °C (+32 °F to +104 °F)
Storage Humidity	30%–75% (RH)

Technical Specification	
Model	DHI-VTO4202F-MDB10
System	
Button Type	Mechanical
Number of Buttons	10
Performance	
Casing Material	Aluminum alloy
Port	
Power Output	5 VDC (Provide power for other modules)
General	
Appearance Color	Silver
Power Supply	5 VDC (Provided with power by other modules)
Certifications	CE EMC; CE LVD
Product Dimensions	100.0 mm × 100.0 mm × 26 mm (3.94" × 3.94" × 1.02")
Protection	IK07; IP65 (Silicone sealant is needed for installation)
Operating Temperature	–30 °C to +60 °C (–22 °F to +140 °F)
Operating Humidity	10%–90% (RH), non-condensing
Operating Environment	Outdoor
Operating Altitude	0 m–3,000 m (0 ft–9,842.52 ft)
Power Consumption	≤0.2 W (standby), ≤0.6 W (working)
Gross Weight	0.33 kg (0.73 lb)
Storage Temperature	0 °C to +40 °C (+32 °F to +104 °F)
Storage Humidity	30%–75% (RH)





Technical Specification	
Model	DHI-VTO4202F-MF
System	
Main Processor	Embedded Processor
Performance	
Casing Material	Aluminum alloy
Port	
Power Output	5 VDC (provides power for other modules)
General	
Appearance Color	Silver
Power Supply	5 VDC (provided by other modules)
Installation	Flush Mount; Surface Mount
Product Dimensions	100 mm × 100 mm × 38.50 mm (3.94" × 3.94" × 1.52")
Protection	IK07; IP65 (silicone sealant is needed for installation)
Operating Temperature	–30 °C to +60 °C (–22 °F to +140 °F)
Operating Humidity	10%–90% (RH)
Power Consumption	≤0.5 W
Gross Weight	0.33 kg (0.73 lb)

Technical Specification	
Model	DHI-VTO4202F-MI
Performance	
Casing Material	Aluminum
General	
Appearance Color	Silver
Power Supply	5 VDC (Provided with power by other modules)
Certifications	CE
Product Dimensions	100.0 mm × 100.0 mm × 28.5 mm (3.94" × 3.94" × 1.12")
Protection	IK07;IP65(silicone sealant is needed for installation)
Operating Temperature	–30°C to +60°C (–22°F to +140°F)
Operating Humidity	10%–90% (RH), non-condensing
Operating Environment	Outdoor
Operating Altitude	0 m–3,000 m (0 ft–9,842.52 ft)
Power Consumption	≤0.5 W
Gross Weight	0.28 kg (0.62 lb)
Storage Temperature	0 °C to +40 °C (+32 °F to +104 °F)
Storage Humidity	30%–75% (RH), non-condensing





Technical Specification	
Model	DHI-VTO4202F-MK
System	
Main Processor	Embedded Processor
Button Type	Mechanical
Performance	
Casing Material	Aluminum alloy
Port	
Power Output	5 VDC (provides power for other modules)
General	
Appearance Color	Black
Power Supply	5 VDC (provided by other modules)
Installation	Flush Mount;Surface Mount
Product Dimensions	100 mm × 100 mm × 31 mm (3.94" × 3.94" × 1.22")
Protection	IK07;IP65(silicone sealant is needed for installation)
Operating Temperature	–30 °C to +60 °C (–22 °F to +140 °F)
Operating Humidity	10%–90% (RH)
Power Consumption	≤0.5 W
Gross Weight	0.32 kg (0.71 lb)

Technical Specification	
Model	DHI-VTO4202F-ML
System	
Main Processor	Embedded Processor
Performance	
Casing Material	Aluminum alloy
Port	
Power Output	5 VDC (provides power for other modules)
General	
Appearance Color	Silver
Power Supply	5 VDC (provided by other modules)
Installation	Flush Mount; Surface Mount
Product Dimensions	100 mm × 50.0 mm × 28.50 mm (3.94" × 1.97" × 1.12")
Protection	IK07; IP65 (silicone sealant is needed for installation)
Operating Temperature	–30 °C to +60 °C (–22 °F to +140 °F)
Operating Humidity	10%–90% (RH)
Power Consumption	≤2 W
Gross Weight	0.19 kg (0.42 lb)





Technical Specification	
Model	DHI-VTO4202F-MN
Performance	
Casing Material	Aluminum alloy
General	
Appearance Color	Silver
Installation	Flush Mount; Surface Mount
Product Dimensions	100 mm × 50.0 mm × 28.50 mm (3.94" × 1.97" × 1.12")
Protection	IK07; IP65 (silicone sealant is needed for installation)
Operating Temperature	–30 °C to +60 °C (–22 °F to +140 °F)
Operating Humidity	10%–90% (RH)
Gross Weight	0.17 kg (0.37 lb)
Power Consumption	≤0.5 W
Gross Weight	0.32 kg (0.71 lb)

Technical Specification	
Model	DHI-VTO4202F-MR1
System	
Main Processor	Embedded Processor
Function	
Card Type	ID card
RFID	
Modulation Type	AM
Frequency Range	125 kHz
Max. Transmission Power	66 dBuA/m @10 m
Performance	
Card Reading Distance	1 cm–3 cm (0.39"–1.18")
Casing Material	Aluminum alloy
Port	
Power Output	5 VDC (provides power for other modules)
General	
Appearance Color	Silver
Power Supply	5 VDC (provided by other modules)
Installation	Flush Mount; Surface Mount
Product Dimensions	100 mm × 50.0 mm × 28.50 mm (3.94" × 1.97" × 1.12")
Protection	IK07; IP65(silicone sealant is needed for installation)
Operating Temperature	–30 °C to +60 °C (–22 °F to +140 °F)
Operating Humidity	10%–90% (RH)
Power Consumption	≤2 W
Gross Weight	0.16 kg (0.35 lb)





Technical Specification	
Model	DHI-VTO4202F-MR
System	
Main Processor	Embedded Processor
Function	
Card Type	IC card
RFID	
Modulation Type	AM
Frequency Range	13.56 MHz
Max. Transmission Power	42 dBuA/m @10 m
Performance	
Card Reading Distance	1 cm–3 cm (0.39"–1.18")
Casing Material	Aluminum alloy
Port	
Power Output	5 VDC (provides power for other modules)
General	
Appearance Color	Silver
Power Supply	5 VDC (provided by other modules)
Installation	Flush Mount; Surface Mount
Product Dimensions	100 mm × 50.0 mm × 28.50 mm (3.94" × 1.97" × 1.12")
Protection	IK07; IP65 (silicone sealant is needed for installation)
Operating Temperature	–30 °C to +60 °C (–22 °F to +140 °F)
Operating Humidity	10%–90% (RH)
Power Consumption	≤2 W
Gross Weight	0.16 kg (0.35 lb)


Technical Specification	
Model	DHI-VTO4202F-MS
System	
Main Processor	Embedded Processor
Performance	
Casing Material	Aluminum alloy
Port	
Power Output	5 VDC (provides power for other modules)
General	
Appearance Color	Silver
Power Supply	5 VDC (provided by other modules)
Installation	Flush Mount; Surface Mount
Product Dimensions	100 mm × 100 mm × 28.50 mm (3.94" × 3.94" × 1.12")
Protection	IK07; IP65 (silicone sealant is needed for installation)
Operating Temperature	–30 °C to +60 °C (–22 °F to +140 °F)
Operating Humidity	10%–90% (RH)
Power Consumption	≤2 W
Gross Weight	0.34 kg (0.75 lb)




Technical Specification

Model	DHI-VTO4202F-MV
Feture	It is used to install the Vigik module.
Performance	
Casing Material	Aluminum alloy
General	
Appearance Color	Silver
Product Dimensions	100.0 mm × 50.0 mm × 6 mm (3.94" × 1.97" × 0.24")
Protection	IK07
Operating Temperature	–30 °C to +60 °C (–22 °F to +140 °F)
Operating Humidity	10%–90% (RH, non-condensing)
Operating Environment	Outdoor
Operating Altitude	0 m–3,000 m (0 ft–9,842.52 ft)
Gross Weight	0.28 kg (0.62 lb)
Storage Temperature	0 °C to +40 °C (+32 °F to +104 °F)
Storage Humidity	30%–75% (RH)


Installation




Dimensions (mm[inch])




DHI-VTO4202F-MB1




DHI-VTO4202F-MB2




DHI-VTO4202F-MB5




DHI-VTO4202F-MF




DHI-VTO4202F-MDB2




DHI-VTO4202F-MI




DHI-VTO4202F-MDB4




DHI-VTO4202F-MK




DHI-VTO4202F-MDB10




DHI-VTO4202F-ML




DHI-VTO4202F-MN



DHI-VTO4202F-MR.DHI-VTO4202F-MR1



DHI-VTO4202F-MS



DHI-VTO4202F-MV

© 2024 Dahua. All rights reserved. Design and specifications are subject to change without notice.
The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.