

G6 180

UVC-G6-180

Datasheet | In The Box | Marketing Images | Accessories | Installation Guide






Overview

Dimensions	136 x 64 x 92 mm (5.6 x 2.5 x 3.6")
IR Night Vision	20 m (65 ft)
Face Recognition	✓
License Plate Recognition	✓
Smart Detections (People, Vehicles, Animals)	✓
Resolution	Dual 4K
Field of View	H: 180°, V: 56.7°
Audio	Two-way audio
Weatherproofing	IP66
Tamper Resistance	IK04
Mounting	Ceiling, Pole, Wedge Mount, Pan Adapter (Included) Camera Junction Box, Arm mount, Dual Mount, Gang Box Mounting Plate (Optional)







Performance

Networking Interface	10/100 MbE RJ45 port
Video	
— Image Settings	Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay, HDR
— Max. Frame Rate	20 FPS
— Resolution	16MP 7680 x 2160 (3.5:1)
Optics	
— Sensor	Dual 1/1.8" 8MP
— Lens	(2) Fixed focal length
— Night Mode	Built-in IR LED illumination and IR cut filter

Hardware

Max. Power Consumption	15W
Supported Voltage Range	37—57V DC
Power Method	PoE+
Processor	Quad-core Arm® Cortex®-A53 based chip
Weight	839 g (1.8 lb)
Enclosure Material	Aluminum alloy, polycarbonate
Mount Material	Polycarbonate, stainless steel
Expansion Slot	MicroSD card
Button	(1) Factory reset
Ambient Operating Temperature	-20 to 50° C (-4 to 122° F)
Ambient Operating Humidity	0 to 90% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC