

iiyama ProLite T2252MSC-B2AG écran plat de PC 54,6 cm (21.5") 1920 x 1080 pixels Full HD LCD Écran tactile Noir

Marque : iiyama

Famille de produit: ProLite

Code produit: T2252MSC-B2AG

Nom du produit : T2252MSC-B2AG

iiyama ProLite T2252MSC-B2AG. Taille de l'écran: 54,6 cm (21.5"), Résolution de l'écran: 1920 x 1080 pixels, Type HD: Full HD, Technologie d'affichage: LCD, Temps de réponse: 5 ms, Format d'image: 16:9, Angle de vision horizontal: 178°, Angle de vision vertical: 178°. Haut-parleurs intégrés. Concentrateur USB intégré, Version du concentrateur USB: 2.0 / 3.2 Gen 1 (3.1 Gen 1). Montage VESA. Couleur du produit: Noir



Display

Display diagonal *	54.6 cm (21.5")
Display resolution *	1920 x 1080 pixels
HD type *	Full HD
Native aspect ratio *	16:9
Display technology *	LCD
Panel type *	IPS
Touchscreen *	✓
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	10
Display brightness (typical)	250 cd/m²
Response time *	5 ms
Screen shape *	Flat
Contrast ratio (typical) *	1000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.7 million colours
Pixel pitch	0.249 x 0.249 mm
Horizontal scan range	30 - 83 kHz
Viewable size, horizontal	47.9 cm
Viewable size, vertical	26 cm
Surface hardness	7H

Performance

NVIDIA G-SYNC *	✗
AMD FreeSync *	✗
Low Blue Light technology	✓
Palm rejection	✓

Multimedia

Built-in camera *	✗
-------------------	---

Design

Product colour *	Black
------------------	-------

Ports & interfaces

Built-in USB hub *	✓
USB hub version	2.0 / 3.2 Gen 1 (3.1 Gen 1)
Number of upstream ports	2
HDMI *	✓
HDMI ports quantity	1
DisplayPorts quantity	1
HDCP	✓

Ergonomics

VESA mounting *	✓
Panel mounting interface	100 x 100 mm
Cable lock slot *	✓
Cable lock slot type	Kensington
Height adjustment *	✗
Tilt adjustment	✓
Tilt angle range	-5 - 90°

Power

Power consumption (typical) *	13 W
Power consumption (standby) *	1.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal

Multimedia		Power	
Number of speakers	2	European Product Registry for Energy Labelling (EPREL) code	1556636
RMS rated power	4 W	Weight & dimensions	
Built-in speaker(s) *	✔		
		Width (with stand)	493.5 mm
		Depth (with stand)	239.5 mm
		Height (with stand)	361.5 mm
		Weight (with stand)	4.5 kg



4948570125180

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-MAY-2025. Prints or copies of Information are only valid on the printed Publication date