

iivama ProLite T1532MSC-B1S écran plat de PC 38,1 cm (15") 1024 x 768 pixels XGA LCD Écran tactile Noir

Marque : iivama

Famille de produit: ProLite

Code produit: T1532MSC-B1S

Nom du produit : T1532MSC-B1S

iivama ProLite T1532MSC-B1S. Taille de l'écran: 38,1 cm (15"), Résolution de l'écran: 1024 x 768 pixels, Type HD: XGA, Technologie d'affichage: LCD, Temps de réponse: 8 ms, Format d'image: 4:3, Angle de vision horizontal: 176°, Angle de vision vertical: 176°. Haut-parleurs intégrés. Montage VESA. Couleur du produit: Noir



Display		Ports & interfaces	
Display diagonal *	38.1 cm (15")	HDMI *	✓
Display resolution *	1024 x 768 pixels	HDMI ports quantity	1
HD type *	XGA	DisplayPorts quantity	1
Native aspect ratio *	4:3	Headphone out *	✗
Display technology *	LCD	HDCP	✓
Panel type *	TN		
Touchscreen *	✓		
Touchscreen technology	Projected capacitive system		
Touch technology	Multi-touch		
Number of simultaneous touchpoints	10		
Display brightness (typical)	350 cd/m²		
Response time *	8 ms		
Screen shape *	Flat		
Contrast ratio (typical) *	800:1		
Viewing angle, horizontal	176°		
Viewing angle, vertical	176°		
Pixel pitch	0.297 x 0.297 mm		
Viewable size, horizontal	30.4 cm		
Viewable size, vertical	22.8 cm		
Digital horizontal frequency	31 - 60 kHz		
Performance		Ergonomics	
NVIDIA G-SYNC *	✗	VESA mounting *	✓
AMD FreeSync *	✗	Panel mounting interface	100 x 100 mm
		Cable management	✓
		Cable lock slot *	✓
		Cable lock slot type	Kensington
		Height adjustment *	✗
		Tilt adjustment	✓
		Tilt angle range	-5 - 90°
Multimedia		Power	
Number of speakers	2	Energy efficiency class (SDR) *	E
RMS rated power	2 W	Power consumption (typical) *	16 W
Built-in speaker(s) *	✓	Power consumption (standby) *	1.5 W
Built-in camera *	✗	Power consumption (off)	0.3 W
		AC input voltage	100 - 240 V
		AC input frequency	50/60 Hz
		Power supply type	Internal
		European Product Registry for Energy Labelling (EPREL) code	1547232
		Weight & dimensions	
		Width (with stand)	351 mm
		Depth (with stand)	200 mm
		Height (with stand)	306.5 mm

Design		Weight & dimensions	
Product colour *	Black	Weight (with stand)	3.7 kg
Ports & interfaces		Packaging content	
Built-in USB hub *	✗	Cables included	Audio, DisplayPort, HDMI, Power, USB
USB Touch port	✓	Quick start guide	✓
VGA (D-Sub) ports quantity	1	Other features	
		International Protection (IP) code	IP54



4948570122097

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-MAY-2025. Prints or copies of Information are only valid on the printed Publication date