

iivama TF2238MSC-B1 Écran d'affichage dynamique Carte A numérique 55,9 cm (22") LED 600 cd/m² Full HD Noir Écran tactile

Marque : iivama

Code produit: TF2238MSC-B1

Nom du produit : TF2238MSC-B1

iivama TF2238MSC-B1. Conception du produit: Carte A numérique. Taille de l'écran: 55,9 cm (22"), Technologie d'affichage: LED, Résolution de l'écran: 1920 x 1080 pixels, Luminosité de l'écran: 600 cd/m², Type HD: Full HD, Écran tactile. Couleur du produit: Noir



Display		Design	
Panel type	IPS	VESA mounting *	✓
Display diagonal *	55.9 cm (22")	Panel mounting interface	100 x 100 mm
Display technology *	LED	Bezel width (bottom)	1.98 cm
Display resolution *	1920 x 1080 pixels	Bezel width (side)	1.7 cm
Display brightness *	600 cd/m²	Bezel width (top)	1.98 cm
HD type *	Full HD	Performance	
Touchscreen *	✓	Purpose *	Universal
Touchscreen technology	Projected capacitive system	On Screen Display (OSD) languages	Simplified Chinese, German, English, French, Japanese, Polish, Russian
Native aspect ratio	16:9	HDCP	✓
Response time	5 ms	International Protection (IP) code	IP1X
Contrast ratio (typical)	1000:1	Power	
Viewing angle, horizontal	178°	Power consumption (typical) *	17 W
Viewing angle, vertical	178°	Power consumption (standby) *	1.5 W
Display number of colours	16.7 million colours	Power consumption (off)	0.3 W
Active display area (W x H)	479 x 260 mm	Energy efficiency class (SDR)	D
Display diagonal (metric)	54.5 cm	AC input voltage	100 - 240 V
Horizontal scan range	28 - 160 kHz	AC input frequency	50 Hz
Native refresh rate	60 Hz	Computer system	
Surface hardness	7H	Computer system *	✗
Ports & interfaces		Built-in processor *	✗
HDMI ports quantity *	1	Weight & dimensions	
DVI port *	✗	Display width	512.5 mm
DisplayPorts quantity *	1	Display depth	47 mm
USB port *	✓	Display height	300 mm
USB ports quantity	2	Display weight	5.1 kg
USB version	3.2 Gen 1 (3.1 Gen 1)		
Ethernet LAN *	✗		
Wi-Fi *	✗		

Audio		Packaging data	
Built-in speaker(s) *	✓	Package width	572 mm
Number of built-in speakers	2	Package depth	112 mm
RMS rated power	2 W	Package height	364 mm
Design		Package weight	6.4 kg
Product design *	Digital A-board	Packaging content	
Placement supported *	Indoor	Cables included	HDMI, Power, USB
Orientation	Horizontal/Vertical	Certificates	
Product colour *	Black	Certification	CE, TÜV-Bauart, EAC, RoHS support, ErP, WEEE, REACH, UKCA



4948570121618

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-MAY-2025. Prints or copies of Information are only valid on the printed Publication date