

iivama OTF1616MC-B1 Écran d'affichage dynamique Écran plat de signalisation numérique 39,6 cm (15.6") LCD 1100 cd/m² Full HD Noir Écran tactile

Marque : iivama

Code produit: OTF1616MC-B1

Nom du produit : OTF1616MC-B1

iivama OTF1616MC-B1. Conception du produit: Écran plat de signalisation numérique. Taille de l'écran: 39,6 cm (15.6"), Technologie d'affichage: LCD, Résolution de l'écran: 1920 x 1080 pixels, Luminosité de l'écran: 1100 cd/m², Type HD: Full HD, Écran tactile. Couleur du produit: Noir



Display		Design	
Panel type	VA	Panel mounting interface	100 x 100 mm
Display diagonal *	39.6 cm (15.6")	Performance	
Display technology *	LCD	Purpose *	Universal
Display resolution *	1920 x 1080 pixels	On Screen Display (OSD)	✓
Display brightness *	1100 cd/m²	Number of OSD languages	7
HD type *	Full HD	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, German, English, Spanish, French, Italian, Japanese
Touchscreen *	✓	HDCP	✓
Touchscreen technology	Projected capacitive system	International Protection (IP) code	IP65
Number of simultaneous touchpoints	10	Mean time between failures (MTBF)	60000 h
Native aspect ratio	16:9	Power	
Response time	25 ms	Power consumption (typical) *	24 W
Contrast ratio (typical)	800:1	Power consumption (standby) *	1.5 W
Viewing angle, horizontal	178°	Power consumption (off)	0.3 W
Viewing angle, vertical	178°	Energy efficiency class (SDR)	E
Display number of colours	16.2 million colours	Energy consumption (SDR) per 1000 hours	11 kWh
Pixel pitch	0.179 x 0.179 mm	Energy efficiency scale	A to G
Active display area (W x H)	345.2 x 194.6 mm	Weight & dimensions	
Display diagonal (metric)	39.5 cm	Display width	398.5 mm
Horizontal scan range	31.5 - 67.5 kHz	Display depth	42 mm
Native refresh rate	60 Hz	Display height	246 mm
Surface hardness	7H	Display weight	3 kg
Glass thickness	3.5 mm	Packaging data	
Ports & interfaces		Package width	485 mm
HDMI ports quantity *	1	Package depth	150 mm
HDMI input ports quantity	1	Package height	370 mm
DVI port *	✗	Package weight	4.62 kg
VGA (D-Sub) input ports	1	Packaging content	
DisplayPorts quantity *	1	Remote control included	✓
USB port *	✓	Cables included	AC, DisplayPort, HDMI, USB
Ethernet LAN *	✓		
Ethernet LAN (RJ-45) ports	1		

Design		Operational conditions	
Product design *	Digital signage flat panel	Operating temperature (T-T)	-20 - 60 °C
Placement supported *	Indoor	Certificates	
Orientation	Horizontal/Vertical	Certification	CE, EAC, RoHS support, ErP, WEEE, cULus, REACH, UKCA
Product colour *	Black		
Screen shape	Flat		
VESA mounting *	✓		



4948570123742

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-MAY-2025. Prints or copies of Information are only valid on the printed Publication date