# DS-2CD2143G2-LI(S)(2U)

## 4 MP Acusense Smart Hybrid Light Fixed Dome Network Camera







- High quality imaging with 4 MP resolution
- Acusense: Focus on human and vehicle classification based on deep learning
- Smart Hybrid Light: Integrates IR and White lights, 4 supplemental lighting modes
- -2U: Built-in arrayed dual-microphone for real-time high quality audio security
- Clear imaging against strong back light due to 120 dB true WDR technology
- Efficient H.265+ compression technology
- Water and dust resistant (IP67) and vandal-resistant (IK10)

## ▪ Specification

| | |
|---|---|
| **Camera** | |
| Image Sensor | 1/3" Progressive Scan CMOS |
| Max. Resolution | 2688 × 1520 |
| Min. Illumination | Color: 0.005 Lux @ (F1.6, AGC ON), 0 Lux with light |
| Shutter Time | 1/3 s to 1/100,000 s |
| Day & Night | IR cut filter |
| Angle Adjustment | Pan: 0° to 355°, tilt: 0° to 75°, rotate: 0° to 355° |
| **Lens** | |
| Lens Type | Fixed focal lens, 2.8 and 4 mm optional |
| Focal Length & FOV | 2.8 mm, horizontal FOV 104°, vertical FOV 57°, diagonal FOV 122°<br>4 mm, horizontal FOV 84°, vertical FOV 45°, diagonal FOV 100° |
| Lens Mount | M12 |
| Iris Type | Fixed |
| Aperture | F1.6 |
| Depth of Field | 2.8 mm: 1.4 m to ∞<br>4 mm: 1.5 m to ∞ |
| **DORI** | |
| DORI | 2.8 mm, D: 63 m, O: 25 m, R: 12 m, I: 6 m<br>4 mm, D: 78 m, O: 31 m, R: 15 m, I: 7 m |
| **Illuminator** | |
| Supplement Light Type | IR, White Light |
| Supplement Light Range | Up to 30 m |
| Smart Supplement Light | Yes |
| IR Wavelength | 850 nm |
| **Video** | |
| Main Stream | 50 Hz:<br>25 fps (2688 × 1520, 1920 × 1080, 1280 × 720)<br>60 Hz:<br>30 fps (2688 × 1520, 1920 × 1080, 1280 × 720) |
| Sub-Stream | 50 Hz: 25 fps (1280 × 720, 640 × 480, 640 × 360)<br>60 Hz: 30 fps (1280 × 720, 640 × 480, 640 × 360) |
| Third Stream | 50 Hz: 10 fps (1920 × 1080, 1280 × 720, 640 × 480, 640 × 360)<br>60 Hz: 10 fps (1920 × 1080, 1280 × 720, 640 × 480, 640 × 360)<br>*Third stream is supported under certain settings. |
| Video Compression | Main stream: H.265/H.264/H.264+/H.265+,<br>Sub-stream: H.265/H.264/MJPEG,<br>Third stream: H.265/H.264,<br>*Third stream is supported under certain settings. |
| Video Bit Rate | 32 Kbps to 8 Mbps |
| H.264 Type | Baseline Profile, Main Profile, High Profile |
| H.265 Type | Main Profile |
| Scalable Video Coding (SVC) | H.264 and H.265 encoding |
| Bit Rate Control | CBR, VBR |
| Region of Interest (ROI) | 1 fixed region for main stream and sub-stream |
| Target Cropping | Yes |

| | |
|---|---|
| **Audio** | |
| Audio Compression | -2U: G.711/G.722.1/G.726/MP2L2/PCM/MP3/AAC-LC |
| Audio Bit Rate | -2U: 64 Kbps (G.711ulaw/G.711alaw)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 160 Kbps (MP2L2)/8 to 320 Kbps (MP3)/16 to 64 Kbps (AAC-LC) |
| Audio Sampling Rate | -2U: 8 kHz/16 kHz/32 kHz/48 kHz |
| Environment Noise Filtering | -2U: Yes |
| **Network** | |
| Protocols | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, WebSocket, WebSockets |
| Simultaneous Live View | Up to 6 channels |
| API | ONVIF (Profile S, Profile G), ISAPI, SDK, ISUP |
| Security | Password protection, complicated password, HTTPS encryption, IP address filter, Security Audit Log, basic and digest authentication for HTTP/HTTPS, TLS 1.1/1.2/1.3, WSSE and digest authentication for Open Network Video Interface |
| User/Host | Up to 32 users<br>3 user levels: administrator, operator, and user |
| Client | iVMS-4200, Hik-Connect, Hik-Central |
| Network Storage | NAS (NFS, SMB/CIFS), Auto Network Replenishment (ANR),<br>Together with high-end Hikvision memory card, memory card encryption and health detection are supported. |
| Web Browser | Plug-in required live view: IE 11,<br>Plug-in free live view: Chrome 80+, Firefox 80+, Edge 89+, Safari 13+,<br>Local service: Chrome 80+, Firefox 80+, Edge 89+, Safari 13+ |
| **Image** | |
| Image Parameters Switch | Yes |
| Image Settings | Rotate mode |
| Day/Night Switch | Day, Night, Auto, Schedule |
| Wide Dynamic Range (WDR) | 120 dB |
| SNR | ≥ 52 dB |
| Image Enhancement | BLC, HLC, 3D DNR |
| Privacy Mask | 8 programmable polygon privacy masks |
| **Interface** | |
| Ethernet Interface | 1 RJ45 10 M/100 M self-adaptive Ethernet port |
| Audio | Built-in Microphone:<br>-2U: Arrayed dual-microphone<br>-S: 1 input (line in), two-core terminal block, max. input amplitude: 3.3 Vpp, input impedance: 4.7 KΩ, interface type: non-equilibrium<br>1 output (line out), two-core terminal block, max. output amplitude: 3.3 Vpp, output impedance: 100 Ω, interface type: non-equilibrium |
| On-Board Storage | Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB |
| Alarm | -S: 1 input, 1 output (max. 12 VDC, 30 mA) |
| Reset Key | Yes |
| **Event** | |
| Basic Event | Motion detection (support alarm triggering by specified target types (human and vehicle)), video tampering alarm, exception |

| | |
|---|---|
| Smart Event | Face detection |
| Linkage | Upload to FTP/NAS/memory card, notify surveillance center, send email, trigger recording, trigger capture, -S: trigger alarm output |
| **Deep Learning Function** | |
| Perimeter Protection | Line crossing, intrusion<br>Support alarm triggering by specified target types (human and vehicle) |
| **General** | |
| Power | 12 VDC ± 25%, 0.6 A, max. 7.2 W, Ø5.5 mm coaxial power plug, reverse polarity protection,<br>PoE: IEEE 802.3af, Class 3, max. 8.5 W |
| Material | Base: aluminum alloy, cover: aluminum alloy |
| Dimension | Ø121.5 mm × 97.6 mm (Ø4.78" × 3.84") |
| Package Dimension | 150 mm × 150 mm × 141 mm (5.91" × 5.91" × 5.55") |
| Weight | Approx. 600 g (1.3 lb.) |
| With Package Weight | Approx. 830 g (1.8 lb.) |
| Storage Conditions | -30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing) |
| Startup and Operating Conditions | -30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing) |
| Language | 33 languages: English, Russian, Estonian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenian, Serbian, Turkish, Korean, Traditional Chinese, Thai, Vietnamese, Japanese, Latvian, Lithuanian, Portuguese (Brazil), Ukrainian |
| General Function | Heartbeat, mirror, flash log, password reset via email, pixel counter, anti-banding |
| **Approval** | |
| EMC | CE-EMC: EN 55032:2015+A1:2020, EN 50130-4:2011+A1:2014, EN IEC 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021,<br>RCM: AS/NZS CISPR 32: 2015,<br>IC: ICES-003: Issue 7,<br>KC: KN32: 2015, KN35: 2015 |
| Safety | CB: IEC 62368-1: 2014+A11,<br>CE-LVD: EN 62368-1: 2014/A11: 2017,<br>BIS: IS 13252 (Part 1): 2010/IEC 60950-1: 2005,<br>LOA: IEC/EN 60950-1 |
| Environment | CE-RoHS: 2011/65/EU,<br>WEEE: 2012/19/EU,<br>Reach: Regulation (EC) No 1907/2006 |
| Protection | IP67: IEC 60529-2013, IK10: IEC 62262:2002 |

## ▪ Typical Application

Hikvision products are classified into three levels according to their anti-corrosion performance. Refer to the following description to choose for your using environment.

This model has NO SPECIFIC PROTECTION


| Level | Description |
|---|---|
| Top-level protection | Hikvision products at this level are equipped for use in areas where professional anti-corrosion protection is a must. Typical application scenarios include coastlines, docks, chemical plants, and more. |

| | |
|---|---|
| Moderate protection | Hikvision products at this level are equipped for use in areas with moderate anti-corrosion demands. Typical application scenarios include coastal areas about 2 kilometers (1.24 miles) away from coastlines, as well as areas affected by acid rain. |
| No specific protection | Hikvision products at this level are equipped for use in areas where no specific anti-corrosion protection is needed. |

## ▪ Available Model

DS-2CD2143G2-LI(2.8mm)
DS-2CD2143G2-LI(4mm)
DS-2CD2143G2-LIS2U(2.8mm)
DS-2CD2143G2-LIS2U(4mm)
DS-2CD2143G2-LIS2U(2.8mm)(BLACK)

## ▪ Dimension




Unit: mm (inch)






## ▪ Accessory











### ▪ Optional


| DS-1275ZJ-SUS | DS-2210ZJ-WA-120 | DS-1280ZJ-DM46 | DS-1272ZJ-120B | DS-1272ZJ-120 |
|---|---|---|---|---|
|  |  |  |  |  |
| DS-2280ZJ-WA120 | DS-2200ZJ-WAJ-120 | DS-1276ZJ-SUS | DS-2200ZJ-WA-120 | DS-1271ZJ-120 |

| | | | | |
|---|---|---|---|---|
|  |  |  |  |  |

## ▪ Installation Methods

| | | | | |
|---|---|---|---|---|
| Vertical Pole Mounting DS-1275ZJ-SUS+DS-2200ZJ-WAJ-120 | Vertical Pole Mounting DS-1275ZJ-SUS+DS-1272ZJ-120+DS-1280ZJ-DM46 | Vertical Pole Mounting DS-1275ZJ-SUS+DS-2200ZJ-WA-120 | Vertical Pole Mounting DS-1275ZJ-SUS+DS-1272ZJ-120B | Vertical Pole Mounting DS-1275ZJ-SUS+DS-1272ZJ-120 |
|  |  |  |  |  |
| Vertical Pole Mounting DS-1275ZJ-SUS+DS-1272ZJ-120B+DS-1280ZJ-DM46 | Vertical Pole Mounting DS-1275ZJ-SUS+DS-2200ZJ-WA-120+DS-1253ZJ-M | Vertical Pole Mounting DS-1275ZJ-SUS+DS-1272ZJ-120B+DS-1253ZJ-M | Vertical Pole Mounting DS-1275ZJ-SUS+DS-2200ZJ-WAJ-120+DS-1253ZJ-M | Vertical Pole Mounting DS-1275ZJ-SUS+DS-1272ZJ-120+DS-1253ZJ-M |
|  |  |  |  |  |
| Vertical Pole Mounting DS-1275ZJ-SUS+DS-2280ZJ-WA120 | Pendant Mounting DS-2210ZJ-WA-120 | Pendant Mounting DS-1271ZJ-120 | Pendant Mounting DS-1271ZJ-120+DS-1280ZJ-DM46 | Junction Box DS-1280ZJ-DM46 |
|  |  |  |  |  |
| Junction Box DS-2280ZJ-WA120 | Wall Mounting DS-1272ZJ-120B | Wall Mounting DS-1272ZJ-120B+DS-1253ZJ-M | Wall Mounting DS-1272ZJ-120B+DS-1280ZJ-DM46 | Wall Mounting DS-1272ZJ-120+DS-1253ZJ-M |

| | | | | |
|---|---|---|---|---|
|  |  |  |  |  |
| Wall Mounting DS-1272ZJ-120 | Wall Mounting DS-1272ZJ-120+DS-1280ZJ-DM46 | Wall Mounting DS-2200ZJ-WAJ-120 | Wall Mounting DS-2200ZJ-WAJ-120+DS-1253ZJ-M | Wall Mounting DS-2200ZJ-WA-120 |
|  |  |  |  |  |
| Wall Mounting DS-2200ZJ-WA-120+DS-1253ZJ-M | Corner Mounting DS-1276ZJ-SUS+DS-2200ZJ-WAJ-120 | Corner Mounting DS-1276ZJ-SUS+DS-2280ZJ-WA120 | Corner Mounting DS-1276ZJ-SUS+DS-1272ZJ-120 | Corner Mounting DS-1276ZJ-SUS+DS-1253ZJ-M+DS-2200ZJ-WA-120 |
|  |  |  |  |  |
| Corner Mounting DS-1276ZJ-SUS+DS-1272ZJ-120B+DS-1253ZJ-M | Corner Mounting DS-1276ZJ-SUS+DS-1272ZJ-120B+DS-1280ZJ-DM46 | Corner Mounting DS-1276ZJ-SUS+DS-1272ZJ-120+DS-1253ZJ-M | Corner Mounting DS-1276ZJ-SUS+DS-2200ZJ-WA-120 | Corner Mounting DS-1276ZJ-SUS+DS-1272ZJ-120+DS-1280ZJ-DM46 |
|  |  |  |  |  |
| Corner Mounting DS-1276ZJ-SUS+DS-1272ZJ-120B | Corner Mounting DS-1276ZJ-SUS+DS-2200ZJ-WAJ-120+DS-1253ZJ-M | | | |



See Far, Go Further

www.hikvision.com
support@hikvision.com

© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

HIKVISION®