

PFA7751-B

General Others Bracket

- Sleek design.



Series Overview

The Mounting Bracket works with front-end services, supporting installation methods such as wall mount, pole mount, corner mount and in-ceiling mount. Select brackets are designed to suit complex scenes, making them convenient to use in environments with high temperatures, humidity, frequent vibrations, and in locations that are highly corrosive. These highly reliable brackets are easy to install and use.

Technical Specification

Structure

Casing Material	Plastic
Product Dimensions	130.2 mm × 40.2 mm × 16.0 mm (5.13" × 1.58" × 0.63") (L × W × H)
Net Weight	17 g (0.04 lb)
Gross Weight	25 g (0.06 lb)
Installation	Wall mount (horizontal 15° angled bracket and mounting bracket)
Packaging Dimensions	135.0 mm × 44.5 mm × 21.5 mm (5.31" × 1.75" × 0.85") (L × W × H)

Environment

Operating Temperature	−40 °C to +60 °C (−40 °F to +140 °F)
Operating Humidity	10%–90% (RH), non-condensing
Storage Temperature	−40 °C to +60 °C (−40 °F to +140 °F)
Storage Humidity	10%–90% (RH), non-condensing
Anti-corrosion Level	Basic Protection

Ordering Information

Type	Model	Description
Bracket	PFA7751-B	General Others Bracket
Accessories (Optional)	PFM900-E	Integrated Mount Tester

Dimensions (mm[inch])

